

---

## STEPS TO CONVERT DHCP TO STATIC IP ADDRESS ON CISCO 7905/12

---

Please make sure you have the following information:

1. A valid, unused IP address
2. the IP address of the router/gateway
3. the subnet mask
4. TFTP Server Address: 65-198.112.100

- 
1. Press the globe-like button on the right hand side of the blue scroll button
  2. Choose (3) "Settings" and Press "Select"
  3. Choose (3) "Network Configuration" and press "Select"
  4. Scroll Down to "DHCP Enabled" (option 21) It should say "Yes"
  5. Press \*\*# quickly on the dialpad
  6. A "No" soft button should appear.
  7. Press "No" But DO NOT PRESS SAVE. Save at the end of the process
  8. Scroll Up to "IP Address" (option 6). Press edit.  
Enter the IP Address and press "VALIDATE"
  9. Scroll Down to "Subnet Mask" (option 7). Press edit.  
Enter the IP Address and press "VALIDATE"
  10. Scroll Down to "Default Router 1" (option 10). Press edit.  
Enter the IP Address and press "VALIDATE"
  11. Scroll Up to "TFTP Server" (option 8). If this field is not set press edit.  
Enter the IP Address and press "VALIDATE"
  12. Save first Screen and then save the second screen.

---

**FOR MORE INFORMATION GO TO [WWW.PRESSONE.NET/MANUALS.HTM](http://WWW.PRESSONE.NET/MANUALS.HTM)**

---